



OUR CABLE SUPPIERS



Tycab Australia is a leading specialised manufacturer of the highest quality Oxygen Free and Tinned Copper electrical cable products. Tycab is proudly Australian owned and operated, with over 30 years experience in the industry.



Electra Cables has been manufacturing and supplying quality electrical and electronic cables to Australian industries and communities for power, lighting, and communication for over 40 years. Product quality, appropriate pricing and excellent service have always been the focus of the company.

WIRING LOOMS



RKS has for many years designed and manufactured high quality wiring looms and harnesses [including lighting, trailer wiring and reverse camera looms] to suit its customers' needs. Our low cost manufacturing methods usually ensure significant time and expense savings.

CABLE WIRING ACCESSORIES ALSO AVAILABLE

- ALLIGATOR CLIPS
- BATTERY TERMINALS
- BUSHINGS
- CABLE CUTTERS/STRIPPERS
- CABLE GLANDS
- CABLE LUGS
- CABLE TIES
- CIRCUIT BREAKERS
- CRIMPING TOOLS
- DIODES
- FUSE HOLDERS
- FUSES
- HEATSHRINK
- INSULATION TAPE
- JUNCTION BLOCKS
- RELAYS
- SOLDER
- SPLIT TUBING
- SWITCHES

**Please feel free to contact us on
1300 914 868
to discuss your requirements further.**

AUTOMOTIVE CABLES



SINGLE CORE



	Part number	Stranding	Nominal area mm ²	AMP	LENGTHS (M)	COLOURS
2mm	SC2 (LENGTH/COLOUR)	9/0.30	0.64	3	3, 4, 7, 30, 100, 500, 1000m	BLACK (BK), PINK(P), BROWN(BN), PURPLE(PL), GREEN(GN), RED(R), GREY(GR), WHITE(W), ORANGE(O), YELLOW(Y)
3mm	SC3 (LENGTH/COLOUR)	16/0.30	1.13	10		
4mm	SC4 (LENGTH/COLOUR)	26/0.30	1.85	15		
5mm	SC5 (LENGTH/COLOUR)	41/0.30	3.25	25		
6mm	SC6 (LENGTH/COLOUR)	37/0.4	4.65	50		
2.5mm	5812 (LENGTH/COLOUR)	8/0.32	0.64	5		

TWIN SHEATH



	Part number	Stranding	Nominal area mm ²	AMP	LENGTHS (M)	COLOURS
2mm	TS2 (LENGTH)	9/0.3	0.64	6	30, 100, 500m	BLACK/RED WITH BLACK OUTER SHEATH
3mm	TS3 (LENGTH)	14/0.32	1.13	16		
4mm	TS4 (LENGTH)	23/0.32	1.84	22		
5mm	TS5 (LENGTH)	41/0.32	3.25	29		
6mm	TS6 (LENGTH)	57/0.32	4.59	38		

MULTICORE



	Part number	Stranding	Nominal area mm ²	CORE COLOURS	AMP	LENGTHS (M)	COLOURS
3 CORE	MC3 (LENGTH)	3x13/0.30	0.92	WHITE, YELLOW, RED	14	30, 100, 500m	BLACK OUTER SHEATH
4 CORE	MC4 (LENGTH)	4x13/0.30	1.92	WHITE, YELLOW, RED, GREEN	15		
5 CORE	MC5 (LENGTH)	5x9/0.3	0.64	WHITE, YELLOW, RED, GREEN, BROWN	7		
5 CORE/3mm	MC5 (LENGTH /3MM)	5x13/0.3	0.92	WHITE, YELLOW, RED, GREEN, BROWN	11		
7 CORE	MC7 (LENGTH)	7x13/0.3	0.92	WHITE, YELLOW, RED, GREEN, BROWN, BLUE, BLACK	6		
7 CORE/3MM	MC7 (LENGTH /3MM)	7x13/0.3	0.92	WHITE, YELLOW, RED, GREEN, BROWN, BLUE, BLACK	10		
7 CORE/4MM	MC7 (LENGTH /4MM)	7x26/0.3	1.84	WHITE, YELLOW, RED, GREEN, BROWN, BLUE, BLACK	14		
7 CORE/6MM	MC7 (LENGTH /6MM)	7x65/0.32	5.23	WHITE, YELLOW, RED, GREEN, BROWN, BLUE, BLACK	55		
FLAT 5, 7 CORE	MC530/FLAT & MC730/FLAT						



1300 914 868
6 Jarrah Drive Braeside VIC 3195
sales@rkssales.com.au



6326 1813
5/190 Invermay Rd, Invermay 7248
rkstas@rkssales.com.au

BATTERY AND STARTER (SINGLE CORE)



	Part number	Nominal area mm ²	Stranding	AMP	
000B&S	000B&S (LENGTH/COLOUR)	83.9	1035/0.32	335	LENGTHS (M) 30, 100, 500m
00B&S	00B&S (LENGTH/COLOUR)	64.15	798/0.32	292	
0B&S	0B&S (LENGTH/COLOUR)	49	608/0.32	246	COLOURS BLACK OR RED
1B&S	1B&S (LENGTH/COLOUR)	39.55	492/0.32	210	
2B&S	2B&S (LENGTH/COLOUR)	32.07	399/0.32	188	
3B&S	3B&S (LENGTH/COLOUR)	26.45	329/0.32	168	
4B&S	4B&S (LENGTH/COLOUR)	20.26	252/0.32	135	
6B&S	6B&S (LENGTH/COLOUR)	13.5	168/0.32	103	
8B&S	8B&S (LENGTH/COLOUR)	7.71	0.96/0.32	74	

BATTERY AND STARTER (TWIN CORE)



	Part number	Nominal area mm ²	Stranding	AMP	LENGTHS (M)	COLOURS: BLACK/RED WITH BLACK OUTER SHEATH WITH OR WITHOUT TRACER
6B&S	6B&S (LENGTH)	13.5	168/0.32	164.8	50, 100m	
8B&S	8B&S (LENGTH)	7	100/0.3	85		

TWIN SHEATH FIGURE 8 SPEAKER WIRE



	Part number	Nominal area mm ²	Stranding	AMP	LENGTHS (M)	COLOURS AVAILABLE IN VARIOUS COLOURS
3mm	TCF83 (LENGTH)	1.13	16/0.3	10	30, 100m	
4mm	TCF84 (LENGTH)	1.84	23/0.32	15		

GAS WIRE (DOUBLE INSULATED)



	Part number	Nominal area mm ²	Stranding	AMP	LENGTHS (M)	COLOURS BLACK OUTER SHEATH
3mm	GW3 (LENGTH)	1.13	16/0.3	20	30, 100, 500m	
4mm	GW4 (LENGTH)	1.85	26/0.3	28		
5mm	GW5 (LENGTH)	3.8	41/0.32	37		
6mm	GW6 (LENGTH)	4.35	37/0.43	48		

MARINE



	Part number	Nominal area mm ²	Stranding	LENGTHS (M)	COLOURS	AMP
2mm	MAR221/50	0.5	16/0.2	50, 100m	BLACK/RED WITH WHITE OUTER SHEATH	7
3mm	MAR321/50	1.13	14/0.32	50, 100m	BLACK/RED WITH WHITE OUTER SHEATH	16
4mm	MAR421/50	1.8	23/0.32	50, 100m	BLACK/RED WITH WHITE OUTER SHEATH	22
6mm	MAR621/50	4.5	57/0.2	50, 100m	BLACK/RED WITH WHITE OUTER SHEATH	38
MARINE B&S				SINGLE AND TWIN CORE 30m	RED, BLACK	
MARINE FIG 8				50m	RED/BLACK	
MARINE MULTICORE				5, 7 CORE AND 0.5, 1.0, 1.84 mm ² 50m	WHITE OUTER SHEATH	

SPECIALITY CABLE



	PART NO.	LENGTHS	OTHER DETAILS
WELDING	ZW MM ²	50, 100m	10, 16, 25, 35, 50, 70mm ²



SECURITY CABLE	SEC	100m	4, 8 CORE FIG 8 GREY OR WHITE
-----------------------	-----	------	-------------------------------



BUILDING WIRE	SRF	100m	240V SINGLE CORE TRACE, FLAT WHITE AND BLACK
----------------------	-----	------	--



SPEAKER/HOME THEATRE	VARIOUS	4, 7, 50, 100m	FIG 8 2mm 3mm 4mm. GREY/BLACK, GREY/WHITE
-----------------------------	---------	----------------	---



HIGH TENSION	HT	30m	7mm
---------------------	----	-----	-----



DATA CABLE	EAS	100, 250m	SHIELDED 4-12 CORE
-------------------	-----	-----------	--------------------



IRRIGATION	WMW9703BL100	100m	0.5mm ² , 9 CORE BLUE
-------------------	--------------	------	----------------------------------



COAX	RG6	100m	50,75 OHM
-------------	-----	------	-----------



TRACE CABLE	SC MM (LENGTH/COLOURS)	30, 100mm	SINGLE CORE IN VARIOUS DIAMETERS AND COLOURS
--------------------	------------------------	-----------	--

AUTOMOTIVE CABLE GENERAL SPECIFICATIONS



Conductor:	Oxygen free Plain annealed copper
Insulation:	PVC V75 or V90
Sheath:	PVC 4V-75
Voltage:	100V DC or 32V AC and must not be connected to mains power
Standards:	AS/NZS 1125 (Conductor) and AS/NZS 3808 (PVC)